



IP PA Horn Speaker 15W (ST-15HSR)

SIPTOK IP PA Horn Speaker 15W (ST-15HSR) is perfect for outdoor environments in most climates. It allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general voice messages. Built-in memory supports pre-recorded messages, or security personal can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound. Open standards support easy integration with network video, access control, analytics, and VoIP (supporting SIP). SIPTOK ST-15HSR is a standalone unit that can be placed almost anywhere, which supports a flexible, scalable and cost-effective approach to system design.

1. Produce Loud & excellent sound
2. All-in-one speaker system
3. Simple installation with PoE
4. Design for installation at outdoor locations
5. 48K OPUS Audio Codec enables excellent sound quality
6. Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP
7. Compatible with IP Camera VMS via ONVIF
8. Support Pre-recorded messages
9. Support HTTP API for alarm in transmit



Specifications:

Audio

Codec	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8kHz, G.711 PCMA 8 kHz
-------	--

Speaker

Impedance	8Ω
Band Width	275-7,000Hz (±3 dB)
Amplifier	Built-in Class D Amplifier
SPL at 1 kHz	106dB/1W/1m 118dB/15W/1m
THD	<0.5% at 1KHz
Signal to Noise Ratio	88dB

Network

Security	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP/IP, UDP, ARP, TFTP, NFS, NTP, FTP, ICMP, SSH, SSL, DNS, SNTP

© Copyright Soniceyes Tech Solution Pvt Ltd. All rights reserved.

Any unauthorised reproduction or use of logos, images or design elements is strictly prohibited by law.
No part of this compilation may be reproduced in any manner or translated without written permission.










SONICEYES TECH SOLUTION PVT LTD

N-189, Sector 2, DSIIIDC, Bawana Industrial Area, Delhi – 110039

Phone No: +91 11-41641379, +91 85905 28734

E-mail: sales@siptok.in, sales@siptok.co.in

Website: www.siptok.in, www.siptok.co.in

Network Interface	10/100 Base-TX, RJ45
VoIP	Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast, ONVIF Codec: OPUS, MP3, G.722, PCMU, PCMA
General	
Operating Temperature	-10°C ~ 65°C
Operating Humidity	5% to 85%
Material	ABS (UV Protected)
Rated Power	15W
Power Supply	POE/12V-2A
Installation	Pole/Wall Mount using Speaker's Bracket
Dimensions	253x152 (L265) mm
Net Weight	1.60 Kg
Languages	English
Standard Warranty	1 year
Standards	IS/IEC:60947-1, Industrial Grade
Make	
Protection	 
Approvals & Compliances	     
Package Includes	IP PA Horn Speaker 15W, Bracket, User Manual, Adapter (on request)

© Copyright Soniceyes Tech Solution Pvt Ltd. All rights reserved.
Any unauthorised reproduction or use of logos, images or design elements is strictly prohibited by law.
No part of this compilation may be reproduced in any manner or translated without written permission.

SONICEYES TECH SOLUTION PVT LTD
N-189, Sector 2, DSIIIDC, Bawana Industrial Area, Delhi – 110039
Phone No: +91 11-41641379, +91 85905 28734
E-mail: sales@siptok.in, sales@siptok.co.in
Website: www.siptok.in, www.siptok.co.in