



IP PA Horn Speaker 60W (ST-60HSR)

SIPTOK IP PA Horn Speaker 60W (ST-60HSR) is perfect for outdoor environments in most climates. It allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general voice messages. Built-in memory supports pre-recorded messages, or security personal can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound. Open standards support easy integration with network video, access control, analytics, and VoIP (supporting SIP). SIPTOK ST-60HSR is a standalone unit that can be placed almost anywhere, which supports a flexible, scalable and cost-effective approach to system design.

1. Produce Loud & excellent sound
2. All-in-one speaker system
3. Simple installation with PoE
4. Design for installation at outdoor locations
5. 48K OPUS Audio Codec enables excellent sound quality
6. Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP
7. Compatible with IP Camera VMS via ONVIF
8. Support Pre-recorded messages
9. Support HTTP API for alarm in transmit



Specifications:

Audio

Codec: OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8kHz, G.711 PCMA 8 kHz

Speaker

Impedance	16Ω
Freq. Response/Band Width	180-7,000Hz (±3 dB)
Amplifier	Built-in Class D Amplifier
SPL at 1 kHz	113dB/1W/1m 128dB/40W/1m
THD	<0.5% at 1KHz
Signal to Noise Ratio	95dB

Network

Security:	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP/IP, UDP, ARP, TFTP, NFS, NTP, FTP, ICMP, SSH, SSL, DNS, SNTP

© Copyright Soniceyes Tech Solution Pvt Ltd. All rights reserved.
Any unauthorised reproduction or use of logos, images or design elements is strictly prohibited by law.
No part of this compilation may be reproduced in any manner or translated without written permission.









SONICEYES TECH SOLUTION PVT LTD

N-189, Sector 2, DSIIIDC, Bawana Industrial Area, Delhi – 110039

Phone No: +91 11-41641379, +91 85905 28734

E-mail: sales@siptok.in, sales@siptok.in

Website: www.siptok.in, www.siptok.co.in

Network Interface	10/100 Base-TX, RJ45
VoIP	Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast, ONVIF Codec: OPUS, MP3, G.722, PCMU, PCMA
Network	
Operating Temperature	-10°C ~ 65°C
Operating Humidity	5% to 85%
Material	ABS (UV Protected)
Rated Power	60W
Power Supply	POE++/220V
Installation	Pole/Wall Mount using Speaker's Bracket
Dimensions	400x200 (L385) mm (Speaker) & 24x15x7.5 mm (Controller)
Net Weight	3.20 Kg (Speaker) & 1 Kg (Controller)
Languages	English
Standard Warranty	1 year
Make	
Protection	 
Approvals & Compliances	     
Package Includes	IP PA Horn Speaker 60W, Controller, Bracket, User Manual, Adapter (on request)

© Copyright Soniceyes Tech Solution Pvt Ltd. All rights reserved.
Any unauthorised reproduction or use of logos, images or design elements is strictly prohibited by law.
No part of this compilation may be reproduced in any manner or translated without written permission.

SONICEYES TECH SOLUTION PVT LTD
N-189, Sector 2, DSIIIDC, Bawana Industrial Area, Delhi – 110039
Phone No: +91 11-41641379, +91 85905 28734
E-mail: sales@siptok.in, sales@siptok.in
Website: www.siptok.in, www.siptok.co.in