



IP PBX (ST-PBX-50U) With Embedded Software

SIPTOK IP PBX (ST-PBX-50U) is embedded with a specifically designed software to control the IP Devices and provide unified communication solutions. The Backbone is designed and tested 24x7 in extreme industrial environments for rugged usage. The operating system is designed on UNIX platform to work seamlessly for virus free and crash free usage.

1. Support Trunk Line
2. Communication with Mobile App
3. Zone Wise Intercom
4. Remote Volume Control
5. Realtime Status of IP Devices
6. Realtime Tracking
7. Integration with other IP Systems
8. Integration with different sensors like Fire Alarm



Specifications:

System

Maximum Number of Devices Support	500
Maximum Parallel Intercom/Announcement support	50
Groups/Zones	Unlimited
Playlists	Unlimited
Music Files	Unlimited
Client Operators	Unlimited

Audio

Codec	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8kHz, G.711 PCMA 8 kHz
Streaming	Mp3 sampling rate 8 -48kHz, bit rate 64 – 320kbps, mono or stereo

Network

Security	Password protection, IP address filtering, Digest authentication, User access log, firewall
----------	---

© Copyright Soniceyes Tech Solution Pvt Ltd. All rights reserved.

Any unauthorised reproduction or use of logos, images or design elements is strictly prohibited by law.
No part of this compilation may be reproduced in any manner or translated without written permission.

SONICEYES TECH SOLUTION PVT LTD

N-189, Sector 2, DSIIIDC, Bawana Industrial Area, Delhi – 110039

Phone No: +91 11-41641379, +91 85905 28734

E-mail: sales@siptok.in, sales@siptok.in

Website: www.siptok.in, www.siptok.co.in

Network Protocol	SIP, HTTP, HTTPS, IPv4, DHCP, RTSP, RTP, RTCP, TCP/IP, UDP, ARP, SNMP, TFTP, NFS, NTP, FTP, ICMP, SSH, SSL, DNS, SNTP
Ethernet Interface	10/100 Base-TX, RJ45
VoIP	Support for SIP protocol for integration with VoIP system
General	
CPU	3.7 GHz Intel Processor
RAM	4 GB DDR3L
Storage	128 GB SSD
USB Interface	1xUSB3.0 + 1xUSB2.0
Power Supply	220V AC
Installation	Plug-in the Power and Connect with Network using RJ45
Dimensions	435X350X89 mm
Net Weight	5.90 Kg
Languages	English
Standard Warranty	3 years
Make	
Approvals & Compliances	     
Package Includes	IP PBX, Power Cable, User Manual

© Copyright Soniceyes Tech Solution Pvt Ltd. All rights reserved.
Any unauthorised reproduction or use of logos, images or design elements is strictly prohibited by law.
No part of this compilation may be reproduced in any manner or translated without written permission.

SONICEYES TECH SOLUTION PVT LTD
N-189, Sector 2, DSIIIDC, Bawana Industrial Area, Delhi – 110039
Phone No: +91 11-41641379, +91 85905 28734
E-mail: sales@siptok.in, sales@siptok.in
Website: www.siptok.in, www.siptok.co.in