



IP Phone Basic (ST-SP10)

IP Phone Basic (ST-A2I) is a steadfast and high endurance SIP Phone that can be used for multiple applications such as Intercom, Broadcasting, SIP Paging, Incoming & outgoing Calls, Our SIP Phone is a real innovation in design and performance.



Specifications:

Audio

Codec: OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8kHz, G.711 PCMA 8 kHz

Audio Streaming MP3 sampling rate 8 – 48KHz, bit rate 64 – 320kbps, mono or Stereo

Network

Security: Password protection, IP address filtering, Digest authentication, User access log, firewall

Network Protocol SIP, ONVIF, HTTP, HTTPS, IPv4, DHCP, RTSP, RTP, RTCP, TCP/IP, UDP, ARP, SNMP, TFTP, NFS, NTP, FTP, ICMP, SSH, SSL, DNS, SNTP

Network Interface 10/100 Base-TX, RJ45

General

Material ABS

Power Supply Corded Electric

Display 132x48 pixel backlit

Dimensions 209x184x76 mm

Net Weight 730 gm

Languages English

Standard Warranty 1 year

Make



Approvals & Compliances



Package Includes IP Phone (Basic), Adapter, User Manual

© Copyright Soniceyes Tech Solution Pvt Ltd. All rights reserved.

Any unauthorised reproduction or use of logos, images or design elements is strictly prohibited by law.
No part of this compilation may be reproduced in any manner or translated without written permission.

SONICEYES TECH SOLUTION PVT LTD

N-189, Sector 2, DSIIIDC, Bawana Industrial Area, Delhi – 110039

Phone No: +91 11-41641379, +91 85905 28734

E-mail: sales@siptok.in, sales@siptok.co.in

Website: www.siptok.in, www.siptok.co.in